

Think Within.



RhinoLaryngoscope System

Specification Data Sheet



Safety	Standard	Class II, 21 CFR 874.4760 / Nasopharyngoscope (Flexible Or Rigid) And Accessories / EOB;				
	Operating Storage and transportation	Temperature: 5°C-40 °C, atmospheric pressure: 700hPa-1060hPa, humidity: ≤93%. Temperature: 0°C-45 °C, atmospheric pressure: 700hPa-1060hPa, humidity: 30%-95%.				
Single-use RhinoLaryngoscope	Model	RH-M22	RH-M32A	RH-M32	RH-M40	RH-M40H
	Compatible image processor model	MS-8				
	Type	Flexible	Flexible	Flexible	Flexible	Flexible
	Image sensor	CMOS (Complementary Metal Oxide Semiconductor) Chip-on-tip				
	View angle	120°±10°	120°±10°	120°±10°	120°±10°	120°±10°
	Direction of view	0°±10°	0°±10°	0°±10°	0°±10°	0°±10°
	View depth	3-50 mm	3-50 mm	3-50 mm	3-50 mm	3-50 mm
	Insertion tube diameter	2.2 mm	3.1 mm	3.1 mm	4.0 mm	4.0 mm
	Maximum size of insertion portion	2.3 mm	3.2 mm	3.2 mm	4.1 mm	4.5 mm
	Working channel	/	/	1.2 mm	2.0 mm	1.2 mm
	Bending angle(up/down)	210°/210°	210°/210°	210°/210°	210°/210°	210°/210°
	Working length	350 mm±10%	350 mm±10%	350 mm±10%	350 mm±10%	350 mm±10%
	Total length	605 mm±10%	605 mm±10%	605 mm±10%	605 mm±10%	605 mm±10%
	Weight	≤0.28 Kg	≤0.28 Kg	≤0.28 Kg	≤0.28 Kg	≤0.28 Kg
	Control Button	Two Buttons (User definable functions through the image processor: White Balance, Zoom In/Out, Snapshot, Video recording, Freeze, Disabled)				
	Enlarged view of tip 1. CMOS sensor 2. LED light source 3. Instrument channel outlet					
	Instrument channel (Direction from which instruments enter and exit the image)					

Image Processor	Model	MS-8
	Operating	Temperature: 5°C-40 °C, atmospheric pressure: 800hPa-1060hPa, humidity: 30-80%.
	Storage	Temperature: -10°C-45 °C, atmospheric pressure: 800hPa-1060hPa, humidity: 30%-80%.
	Transportation	Temperature: -20°C-50 °C, atmospheric pressure: 800hPa-1060hPa, humidity: 20%-90%.
	Physical specification	
	Dimensions	386.4 (h) x 253.6 (w) x 38.5 (d) mm
	Weight	2.7 kg
	Display	
	Display size	15.6 inches
	Display resolution	1920*1080 px FHD
	Display type	Color TFT LCD with touch screen
	Display orientation	Support dual-view display, rotation function
	Function of Setting	
	Scope button configuration	Function of A/B: White Balance, Zoom In/Out, Snapshot, Video recording, Freeze, Disabled
	Image adjustment	LED Level/Sharpness/Color Tone/Contrast
	Language	Simplified Chinese, English, French, German, Spanish, Portuguese, Norwegian, Swedish, Finnish, Italian, Russian, Traditional Chinese, Japanese, Persian, Romanian
	Pre-recording	Control function of Patient Information Management on/off
	Image border	
	Output interface	
	USB I (USB-A)	For data transfer, system upgrades, printer connection, keyboard & mouse connection
	Digital video output	HDMI, DVI and SDI for connectivity to the external monitor
	Output resolution	Full HD 1920*1080 px
	Input interface	
	VL-port (USB-C)	For connection with endoscopes supporting USB Type-C cables
	Endoscope port	For connection with endoscope supporting edge connector cables
	DC	Power supply
	USB II (USB-A)	For developers only
	Recording function	
	Recording format	JPG or BMP for photograph, MP4 for video (Low/Medium/High)
	Memory capacity	Built-in SD card, 64 GB
	Audio recording	Supported
	File & Folder Renaming	Supported
	Case Templates	Supported
	Power supply	
	Power adapter input	AC 100-240V 50/60Hz, 1.5A Max (Battery charger)
	Battery	Rechargeable lithium battery, DC 7.4V, 9500 mAh
	Battery continuous working time	Maximum 5 hours
	Mounting interface	
	Mounting interface standard	VESA MIS-D 100/75, C compliant displays with mounting interface
	Cleaning and Disinfection	
	Recommended cleaning method	It is recommended to wipe with water mixed with detergents or enzymatic solution for cleaning.
	Recommended disinfection method	It is recommended to wipe with 75% medical alcohol for disinfection.



DISTRIBUTED BY:

EndoTherapeutics.com • Toll Free: **844.400.ENDO** (3636)
 Endo-Therapeutics, Inc. • 15251 Roosevelt Blvd, Suite 204 • Clearwater, FL 33760

EndoT® and Think Within® are trademarks of Endo-Therapeutics, Inc. ©2025 Endo-Therapeutics, Inc. All rights reserved. MKT-028 Rev B